

MORITZ

INTERNATIONAL INC.

F-SERIES

Heavy-duty deck-over-flatbed trailers

**BUILT
TO LAST
PERFORMANCE**

Best in class trailers:

- ▲ Flatbed
- ▲ Dump
- ▲ Equipment
- ▲ Landscape
- ▲ Stock/Horse

Moritz International, Inc.
665 N. Main Street
Mansfield, OH 44902
www.moritzint.com

Gooseneck Flatbed

FBG+5-20



STANDARD TOOLBOX
Built with diamond plate steel- all models.



ADJUSTABLE DOVETAIL
Easily convert the dovetail to lay flat with the deck of the trailer providing additional hauling space.



SPRING LOADED RAMPS
Spring loaded ramps lift easily, but are built tough with heavy-duty 4" channel.



SIDE TURN SIGNALS
Mid-trailer side turn signals are standard on all Moritz F-Series trailers.



MORITZ F-SERIES

Heavy-duty deck-over flatbed trailers

The F-Series trailer has been engineered and manufactured to withstand the demanding everyday duties that are required from a trailer. With a new one-piece gooseneck, our F-Series is stronger, sleeker, and provides a smoother ride than our competitors. Features such as a 3" lower deck height, an adjustable dovetail, standard toolbox, and a multi-stage painting process make the Moritz F-Series the best in its class.

As a family-owned manufacturer with more than 30 years of service, Moritz has earned a reputation for quality workmanship, dedicated service and built-to-last performance. Moritz International trailers are the best built trailers the industry has to offer.

Moritz trailers are sold exclusively through an Authorized Dealer Network. For dealer information, call us at (419) 526-5222 or visit our website at www.moritzint.com.



INTEGRATED STEPS
Steps on both sides of the trailer allow for easy access to the deck.



VERTICAL RAMP BARS
Our optional vertical ramp bars give you additional hauling space.

MORITZ F-SERIES HEAVY-DUTY DECK-OVER-FLATBED TRAILERS

STANDARD SPECIFICATIONS

deck height	low profile: 33" standard: 36"
overall width	100"
brakes	electric brakes, all wheels
torsion axles	on 7k and 8k
stake pockets	1/4" x 2" x 4"
tire	16" radial 10-ply rated
wheel	16", 8-bolt
jack(s)	10,000 lb. spring-loaded foot
coupler	2 5/16" adjustable
cross-members	3" channel, approx. 24" spacing on 9k and 10k, approx. 16" spacing
side rails	6" channel w/ rub rail & stake pockets, approx. 24" spacing
safety chains	3/8" w/ latch hook
lights	sealed beam with moisture-resistant connectors
floor	2" treated yellow pine
ramp construction	4" channel x 2" x 3" x 3/16" angle
5' adjustable dovetail	spring-loaded ramps
breakaway kit (with charger)	side turn signals
steps for deck access	tool box - diamond plate

OPTIONS

pintle ring
LED lighting
2 5/16" heavy-duty coupler
no dovetail or ramps
upgrade axles 7k to 7.2k (remains 14,500 GVWR, 2.5" brakes)
upgrade axles 7k to 8k with 17.5" radial tires (17,000 GVWR)
upgrade axles 7k tandem to 7k tri-axle (20,000 GVWR)
upgrade axles 10k dual GD to 10k dual HD
torsion stabilizer
spare tires and wheels
dovetail jack
dual/single-speed jacks
one/two-speed jack or dual/two-speed jacks
electric over hydraulic brakes
vertical ramp bars
third center ramp
no ramps
100" x 80" deck over gooseneck
angle on dovetail, in place of wood

WEIGHT SPECIFICATIONS

	7k gooseneck	7k pintle ring	9k and 10k gooseneck	9k and 10k pintle ring
16'	4900 lbs.	4300 lbs.	5400 lbs.	4800 lbs.
18'	5100 lbs.	4600 lbs.	5800 lbs.	5300 lbs.
20'	5400 lbs.	4800 lbs.	6300 lbs.	5700 lbs.
22'	5700 lbs.	5100 lbs.	6800 lbs.	6200 lbs.
24'	5900 lbs.	5400 lbs.	7200 lbs.	6800 lbs.
26'	6200 lbs.	5600 lbs.	7700 lbs.	7100 lbs.

All weights include 5' dovetail and ramps. If purchasing without dovetail, deduct 1000 lbs.

If substituting 8k axles for 7k, add 300 lbs.

Top deck option weighs approximately 960 lbs.

FRAME & AXLE SPECIFICATIONS

	single wheel	dual wheel
	14,500 GVWR 7k torsion axle	19,000 GVWR 9k spring axle
	17,000 GVWR 8k torsion axle	20,000 GVWR 10k spring axle
16' low-profile	10" @ 12 lbs. w/8" @ 10 lbs. over axles	10" @ 19 lbs. w/8" @ 15 lbs. over axles
16' standard deck	10" @ 12 lbs.	10" @ 19 lbs.
18' low-profile	10" @ 12 lbs. w/8" @ 10 lbs. over axles	10" @ 19 lbs. w/8" @ 15 lbs. over axles
18' standard deck	10" @ 12 lbs.	10" @ 19 lbs.
20' low-profile	10" @ 12 lbs. w/8" @ 10 lbs. over axles	10" @ 19 lbs. w/8" @ 15 lbs. over axles
20' standard deck	10" @ 12 lbs.	10" @ 19 lbs.
22' low-profile	10" @ 12 lbs. w/8" @ 10 lbs. over axles	10" @ 19 lbs. w/8" @ 15 lbs. over axles
22' standard deck	10" @ 12 lbs.	10" @ 19 lbs.
24' standard deck	10" @ 19 lbs.	10" @ 19 lbs.
26' standard deck	10" @ 19 lbs.	10" @ 19 lbs.

MORITZ
INTERNATIONAL INC.
...Quality Trailers

MORITZ INTERNATIONAL, INC.

665 North Main Street, Mansfield, Ohio 44902

Phone (419)526-5222

www.moritzint.com



For God so loved the world, that he gave his only begotten Son, that whosoever believeth in him should not perish, but have everlasting life. John 3:16 KJV

© 2006 Moritz International, Inc. design, specifications, and prices are subject to change without notice. Printed in U.S.A.