



GROUND LOADER



STANDARD SPECIFICATIONS.....

AVAILABLE SIZES: 34', 44', 48', 50', 53'

WIDTH: 102"

HEIGHT: 10'4" OVERALL, 8'6" REAR, 6'9" CENTER, 5'10" NOSE

SUSPENSION: AIR RIDE

WHEELS AND TIRES: 22.5 LOW PROFILE

BACKEND: FULL SWING WITH ROLL UP DOOR

DROPS: FRONT 10", REAR 21"

RAMP: REAR BEHIND DIVIDER

GATES: (1) FRONT DROP, (1) CENTER, (1) REAR DROP, (2) CENTER ON 53'

FLOOR: .115 ALUMINUM DIAMOND PLATE

SIDE CONSTRUCTION: PUNCH PANEL

LANDING GEAR: ALUMINUM DROP LEGS

LIGHTS: LED



REAR DROP RAMP FOR 21" DROP



MANUAL DUMP VALVE



HEAVY DUTY
4" ALUMINUM
HINGES ON
BACK DOOR



EXTRUDED SIDE POSTS
FOR VERTICAL
CLOSURES



RADIUS NOSE DESIGN – WITH
OPTIONAL STAINLESS CORNERS



EASY LOADING, OPEN FLOOR PLAN. GATES POSITIVELY LOCK BACK FLAT AGAINST WALL IN CENTER. GATES AT FRONT AND REAR DROP ARE 2/3 OPENING TO ASSIST IN FUNNELING INTO LOADING AREAS.



FULL SWING BACKEND WITH ROLL UP DOOR FOR FULL WIDTH OPENING



2 PIECE ROOF RAIL PROVIDES CLEAN LOOK OUTSIDE AND INSIDE AS WELL AS PROTECTED AREA FOR WIRING



.115 RIDGED ALUMINUM DIAMOND PLATE FLOOR WITH 3-1/2" TUBULAR CROSS MEMBERS ON 15" CENTERS



Extruded Front Corners Provide Strength and Maximum Inside Clearance

